check by 17 8/25/16

CETIFICATION

SDG No:

FA35794

Site:

BMSMC - Building 5 Area

Humacao, PR

Laboratory:

Accutest, Florida

Matrix:

Groundwater

SUMMARY:

Samples (Table 1) were collected on the BRSMC facility – Building 5 Area. The BMSMC facility is located in Humacao, PR. Samples were taken July 28-29, 2016 and were analyzed in Accutest, Florida that reported the data under SDG No.: FA35794. Results were validated using the latest validation guidelines (July, 2015) of the EPA Hazardous Waste Support Section. The analyses performed are shown in Table 1. Individual data review worksheets are enclosed for each target analyte group. The data sample organic data samples summary form shows for analytes results that were qualified.

In summary the results are valid and can be used for decision taking purposes.

Table 1. Samples analyzed and analysis performed

SAMPLE ID	SAMPLE	MATRIX	ANALYSIS PERFORMED
	DESCRIPTION		
FA35794-1	OSMW-2D	Groundwater	VOA TCL List*
FA35794-2	OSMW-2S	Groundwater	VOA TCL List*
FA35794-3	OSMW-2SD	Groundwater	VOA TCL List*
FA35794-4	OSMW-1D	Groundwater	VOA TCL List*
FA35794-5	OSMW-1S	Groundwater	VOA TCL List*
FA35794-6	EB072816	AQ - Equipment	VOA TCL List*
		Blank	
FA35794-7	TB072816	AQ - Trip Blank	VOA TCL List*
		Water	

Benzene, Methyl Tert Butyl Ether, Tert-Amyl Alcohol

Reviewer Name:

Rafael Infante

Chemist License 1888

Signature:

Date:

August 15, 2016

Prince Information Méndez
LIC # 1888
A 1591712

Run #1

Purge Volume

 $5.0 \, \mathrm{ml}$

Report of Analysis

Page 1 of 1

Client Sa	mple ID:	OSMV	V-2D					
Lab Sam	ple ID:	FA357	94-1			Ι	Date Sampled:	07/28/16
Matrix:		AQ - C	Ground Wa	iter		E	ate Received:	07/30/16
Method:		SW846	8260C			F	ercent Solids:	n/a
Project:		BMSM	IC, Buildii	ng 5 Area, Hum	acao, PR			
	File ID		DF	Analyzed	Ву	Prep Date	Prep Batc	h Analytical Batch
Run #1	J097841	7.D	1	08/01/16	DP	n/a	n/a	VJ5387
Run #2								

Run #2						
CAS No.	Compound	Result	RL	MDL	Units	Q
71-43-2	Benzene	ND	1.0	0.20	ug/l	
1634-04-4	Methyl Tert Butyl Ether	ND	1.0	0.20	ug/l	
75-85-4	Tert-Amyl Alcohol	ND	20	6.0	ug/l	
CAS No.	Surrogate Recoveries	Run# 1	Run# 2	Lim	its	
1868-53-7	Dibromofluoromethane	95%		83-1	18%	
17060-07-0	1,2-Dichloroethane-D4	100%		79-1	25%	
2037-26-5	Toluene-D8	103%		85-1	12%	
460-00-4	4-Bromofluorobenzene	91%		83-1	18%	



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

Report of Analysis

Page 1 of 1

Client Sample ID:	OSMW-2S
Lab Sample ID:	FA35794-2
2 2 2 2	100

AQ - Ground Water Matrix: Method: SW846 8260C

BMSMC, Building 5 Area, Humacao, PR

Date Sampled: 07/28/16 Date Received: 07/30/16

Percent Solids: n/a

Q

	File ID	DF	Analyzed	Ву	Prep Date	Prep Batch	Analytical Batch
Run #1	J0978399.D	1	08/01/16	DP	n/a	n/a	VJ5387
Run #2							

Purge Volume Run #1 $5.0 \, \mathrm{ml}$

Run #2

Project:

CAS No.	Compound	Result	RL	MDL	Units	
71-43-2 1634-04-4 75-85-4	Benzene Methyl Tert Butyl Ether Tert-Amyl Alcohol	ND ND ND	1.0 1.0 20	0.20 0.20 6.0	ug/l ug/l ug/l	
CAS No.	Surrogate Recoveries	Run# 1	Run# 2	Lim	its	
1868-53-7 17060-07-0 2037-26-5	Dibromofluoromethane 1,2-Dichloroethane-D4 Toluene-D8	98% 106% 102%		83-1 79-1 85-1	25%	
460-00-4	4-Bromofluorobenzene	104%		83-1	18%	



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

Report of Analysis

Page 1 of 1

Client Sample ID:	OSMW-2SD
Lab Sample ID:	FA35794-3
Matrix:	AQ - Ground V

AQ - Ground Water

SW846 8260C BMSMC, Building 5 Area, Humacao, PR Date Sampled: 07/28/16 Date Received: 07/30/16

Percent Solids: n/a

Q

j

	File ID	DF	Analyzed	Bv	Prep Date	Pren Batch	Analytical Batch
1	12012				Trep Date	A rop Date	1 may would Devou
Run #1 a	10978431.D	5	08/02/16	DP	n/a	n/a	VJ5389
	30010101.2		00,02,10	171	117 G	147 14	v J0000
D 49							

Run #2

Mcthod:

Project:

Purge Volume Run #1 5.0 ml

Run #2

CAS No.	Compound	Result	RL	MDL	Units
71-43-2 1634-04-4 75-85-4	Benzene Methyl Tert Butyl Ether Tert-Amyl Alcohol	4.2 ND ND	5.0 5.0 100	1.0 1.0 30	ug/l ug/l ug/l
CAS No.	Surrogate Recoveries	Run# 1	Run# 2	Limi	ts
1868-53-7 17060-07-0 2037-26-5 460-00-4	Dibromofluoromethane 1,2-Dichloroethane-D4 Toluene-D8 4-Bromofluorobenzene	91% 100% 105% 100%		83-11 79-12 85-11	25% 1 2 %

(a) Dilution required due to matrix interference (sample foamed).



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

Report of Analysis

Ву

DP

n/a

Page 1 of 1

Client Sample ID:	OSMW-1D
Lab Sample ID:	FA35794-4
Matrix:	AQ - Ground

File ID

J0978401.D

AQ - Ground Water SW846 8260C

DF

1

SW846 8260C BMSMC, Building 5 Area, Humacao, PR

Analyzed

08/01/16

Date Sampled: 07/29/16 Date Received: 07/30/16

Percent Solids: n/a

n/a

Q

Prep Date Prep Batch Analytical Batch

VJ5387

Run #1 Run #2

Method:

Project:

Purge Volume Run #1 5.0 ml

Run #2

CAS No.	Compound	Result	RL	MDL	Units
71-43-2 1634-04-4 75-85-4	Benzene Methyl Tert Butyl Ether Tert-Amyl Alcohol	ND ND ND	1.0 1.0 20	0.20 0.20 6.0	ug/l ug/l ug/l
CAS No.	Surrogate Recoveries	Run# 1	Run# 2	Lim	its
1868-53-7 17060-07-0 2037-26-5	Dibromofluoromethane 1,2-Dichloroethane-D4 Toluene-D8	96% 108% 103%		79-1 85-1	18% 25% 12%
1868-53-7 17060-07-0	Surrogate Recoveries Dibromofluoromethane 1,2-Dichloroethane-D4	96% 108%	Run#	2	83-1 79-1



ND = Not detected

MDL = Method Detection Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

Report of Analysis

Page 1 of 1

C	lient Sample I	D: OSMW-1S
I	ab Sample ID	: FΛ35794-5

Matrix: Method: AQ - Ground Water

SW846 8260C

Date Sampled: Date Received: 07/30/16

07/29/16

Percent Solids: n/a

Project: BMSMC, Building 5 Area, Humacao, PR

File ID Run #1 J0978402.D DF 1

Analyzed By 08/01/16 DP Prep Date n/a

Prep Batch n/a

Analytical Batch VJ5387

Run #2

Purge Volume $5.0 \, ml$

Run #1 Run #2

CAS No. Compound 71-43-2 Benzene 1634-04-4 Methyl Tert Butyl Ether 75-85-4 Tert-Amyl Alcohol

CAS No. Surrogate Recoveries 1868-53-7 Dibromofluoromethane

17060-07-0 1.2-Dichloroethane-D4 2037-26-5 Toluene-D8 460-00-4 4-Bromofluorobenzene

RLMDL Result ND 1.0 0.20

Run#1

96%

104%

101%

100%

0.29 1.0 0.20ND 20 6.0

Run#2

83-118% 79-125% 85-112%

83-118%

Limits

Units

ug/l

ug/l

ug/I

Q

J



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

12 of 291

Report of Analysis

Page 1 of 1

Client Sample ID: EB072816 Lab Sample ID: FA35794-6

Matrix:

AQ - Equipment Blank

Method: Project:

SW846 8260C

BMSMC, Building 5 Area, Humacao, PR

Date Sampled: 07/28/16

Date Received: 07/30/16 Percent Solids: n/a

Q

File ID DF Analyzed By Prep Date Prep Batch **Analytical Batch** Run #1 J0978403.D 1 08/01/16 DP n/a n/a VJ5387

Run #2

Purge Volume 5.0 ml

Run #1 Run #2

CAS No. Compound Result RLMDL Units 71-43-2 Benzene ND 1.0 0.20ug/l 1634-04-4 Methyl Tert Butyl Ether ND 1.0 0.20 ug/l 75-85-4 Tert-Amyl Alcohol ND 20 6.0 ug/I

CAS No. Surrogate Recoveries Run#1 Run#2 Limits Dibromofluoromethane 97% 1868-53-7 83-118% 17060-07-0 1,2-Dichloroethane-D4 104% 79-125% 2037-26-5 Toluene-D8 85-112% 106% 460-00-4 4-Bromofluorobenzene 98% 83-118%



E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

Report of Analysis

Page 1 of 1

Client Sample ID:	TB072816
Lab Sample ID:	FA35794-7

94-7 Matrix: AQ - Trip Blank Water

SW846 8260C

BMSMC, Building 5 Area, Humacao, PR

Date Sampled: 07/22/16 Date Received: 07/30/16

Percent Solids:

Project:		BMSMC,	Building	5 Агеа,	Humacao,	PR

	File ID	DF	Analyzed	Ву	Prep Date	Prep Batch	Analytical Batch
Run #1	J0978404.D	1	08/01/16	DP	n/a	n/a	VJ5387
Dun #2							

Run #2

Run #1

Method:

Purge Volume

 $5.0 \, ml$

Run #2

CAS No.	Compound	Result	RL	MDL	Units	Q
71-43-2 1634-04-4 75-85-4	Benzene Methyl Tert Butyl Ether Tert-Amyl Alcohol	ND ND ND	1.0 1.0 20	0.20 0.20 6.0	ug/l ug/l ug/l	
CAS No.	Surrogate Recoveries	Run# I	Run# 2	Limi	ts	
1868-53-7 17060-07-0 2037-26-5 460-00-4	Dibromofluoromethane 1,2-Dichloroethane-D4 Toluene-D8 4-Bromofluorobenzene	97% 105% 104% 94%		83-1 79-1: 85-1 83-1	25% 12%	



ND = Not detected

MDL = Method Detection Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

N = Indicates presumptive evidence of a compound

TAC:	CLITEGE.			CHAI				_				,			57 605			Part de			<u>_</u> o	F <u>. (</u>
	FL				1-625-678	FAX	407-423		2511					اضوا						from	ш	
City	nt / Reporting Information	Project Home:		Project		tion	TOTAL					3-0	T ₂₈	Req	ented.	Arm're	in (900	IEST C	ODE et	WAS C	3000	Maint Codes
Arabertus Blu	dhelland & Associates	SMERC Plan	e 2A Rainsee A										Ĭ									CW - Chaptry Water WW - Water
Street Address	aldi sr Alminus, Sulto 417	\$head							-70		anney.	***	Ě									SW - States Visite
Chy massic	Units 2	Day		State	Grant Company	,	-11-						12					ш				S1 (Subpo S123-Sudantel
Parchage Parent Cartest	NY B	18677 Hammone		PR	Same A								1			- 1						CH-CH LIC-Other Light
Torry Tayle	lor	623			L													ы				AR-Ar SCL-OperSele
Press 0 814-281-04		Charle Physiological	Ovelog of		2				_		2	P	Julia.					П				WP-Wge FB-Flag (mah.
Engineral Harm		hate 9 Proper Manager			Attendo	<u>. </u>							1			- 1			- 1		1	EB-Equipment (Burk 168-Physic Speck 78-74b (Burk
N. Rhera,	R. Strart, R. O'Rolly, T. Yaylo	r Terry Taylor		Onto the last	<u> </u>		_	_		-		_	18	1				ы				(IN-TOP SHAPE
		1		<u> </u>	Ī			Π,		, i	M.	Till.	ATRICO SME.Y.					ш		- 1		
	eld ID / Point of Cofection	Military	Cala	-			0 40 1400	12 1	1 2	\$ B		18	_			\perp	\perp	Ш			\bot	LAB UMS COLY
08	TUR-SD		7-24-16		NR	GW	3	13	Ц		Ц	Ш	X			_		\sqcup	Ш			
	MW - 25		7-29-16	1718	NK	GW	а	3	Щ	丄	Ц	Щ	X	ļ		_ _		\sqcup		_		
	MW-25D		7-29-16	1730	NR	GW	3	3	11	4	Ц	Щ	X	$oxed{oxed}$	Щ			\bot	\Box	\rightarrow	1	
1.7.1	20V - 1D		7-29-16	1048	10	CIM	3	13	11	1	Ц	Ц	X		\sqcup	4	+	\Box		_	4	
5 09	5MW-15		7-29-16	1150	70	GW	3	3	41	4	Ц	Ш	X	1	\sqcup	+	+	-	-	-	+	
					<u> </u>			₩	-	4	Н	4			-	-	-	\square		\rightarrow	+	
					-			H	++	+	H	₩	+	\vdash	\vdash	-		╂═┤	-	-		
$\vdash \vdash$				 	\vdash	-	-	╁┼	╂	╬	┼┼	╫	+	├	-	+	-	-	-	+	+-	
\vdash						-		╬	+-	+	╁┼	╬	-	\vdash	⊢		- -	+				
100000000000000000000000000000000000000	SO OF THE PARTY OF THE PARTY OF	CONTRACTOR OF	1513 300	Section 201	and the same	100000	Service Co.	Sec.	SHEET S	200			1000		1000		205000	SALES	SECTION	TES IN	ES EUC.	References:
				-	E S																	
7	Turnament Time (Business days)						Det	Deb		-		4.		APPE LA		-0.0	C	Ĩ	Special Special	الوالية واليوا ما المراجعة		
	. 40 Business Days . 10 Business (Says (Say Continue) and		and Phily I Balan			Caman						40° CM	A year									
	Day Atlahi	" ====				FULLTI	(Level)				j 🛶	Ferm			-							
	ny Audio Ny ENGRODICY					MJ Steller Communication) 25%] One	~	٠		Unity re	pat W	FEBRUA, I	At rept" de	Pag 1867-	Ainyl Alc	anol .	
10	NAME OF TAXABLE PARTY				[]		Chambri				F		_								100	
	ny CHEFARENCY E Paylo Tip, diale avalonie VIA Lucinie.						Character Rd Rest	-	topic.	• QC 1		y • Par										
-			mate Controly in		onted b	alow ou	ch there e		e che			bon, In	i ming	territor	44	-		100			No. of Lot	4- 40
· WA	KIPW	7-29-16 /700	Fed	EX				2		_	9	X						3/	14	2	- 5	130Mo
3	State opting by Garages: Step Visign Special S							4							- 1			1	ye.			
Tolkephind I	-	om Viner	the plant by:					-	72	1		0	100 to							60	D ***	~ 4.0
								-	-					_		700						-

. % .

FA35794: Chain of Custody Page 1 of 3

16 of 291

EXECUTIVE NARRATIVE

SDG No:

FA35794

Laboratory:

Accutest, Florida

Analysis:

SW846-8260C

Number of Samples:

7

Location:

BMSMC - Building 5 Area

Humacao, PR

SUMMARY:

Seven (7) samples were analyzed for selected volatile organic compounds (VOCs) by method SW846-8260C. The sample results were assessed according to USEPA data validation guidance documents in the following order of precedence: USEPA Hazardous Waste Support Section SOP No. HW-33A Revision 0 SOM02.2. Low/Medium Volatile Data Validation. July, 2015. The QC criteria and data validation actions listed on the data review worksheets are from the primary guidance document, unless otherwise noted.

Critical issues:

None

Major:

None

Minor:

None

Critical findings:

None

Major findings:

None

Minor findings:

1. Field duplicate RPD for benzene outside laboratory and validation guidance document

control limits. No action taken, sample/duplicate concentration < 5 x SQL.

COMMENTS:

Results are valid and can be used for decision making purposes.

Reviewers Name:

Rafael Infante

Chemist License 1888

Signature:

Date:

August 15, 2016

SAMPLE ORGANIC DATA SAMPLE SUMMARY

Sample ID: FA35794-1

Sample location: BMSMC Building 5 Area

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

Sample ID: FA35794-2

Sample location: BMSMC Building 5 Area

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

Sample ID: FA35794-3

Sample location: BMSMC Building 5 Area

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	4.2	ug/l	1.0	J	J	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

Sample ID: FA35794-4

Sample location: BMSMC Building 5 Area

Sampling date: 7/29/2016

Matrix: AQ - Equipment Blank

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

Sample ID: FA35794-5

Sample location: BMSMC Building 5 Area

Sampling date: 7/29/2016 Matrix: Groundwater

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	0.29	ug/l	1.0	J	J	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

Sample ID: FA35794-6

Sample location: BMSMC Building 5 Area

Sampling date: 7/28/2016

Matrix: AQ - Equipment Blank

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	_	U	Yes

Sample ID: FA35794-7

Sample location: BMSMC Building 5 Area

Sampling date: 7/22/2016 Matrix: AQ - Trip Blank

METHOD: 8260C

Analyte Name	Result	Units	Dilution Factor	Lab Flag	Validation	Reportable
Benzene	1.0	ug/l	1.0	-	U	Yes
Methyl Tert Butyl Ether	1.0	ug/l	1.0	-	U	Yes
Tert-Amyl Alcohol	20	ug/l	1.0	-	U	Yes

		Project Number:_FA35794 Date:July_28-29,_2016 Shipping date:July_29,_2016 EPA Region:2
		ILE ORGANIC PACKAGE platile Data Validation
actions. This document informed decision and in assessed according to precedence: USEPA Haz Low/Medium Volatile Date 1.000	will assist the review better serving the rule of the period of the peri	organics were created to delineate required validation wer in using professional judgment to make more needs of the data users. The sample results were on guidance documents in the following order of the South
		t data package received has rmance data summarized. The data review for VOCs
No. of Samples: Trip blank No.:	8 FA35794-7	Sample matrix:Groundwater
Fauinment blank No :	FΔ3570/L6	

Lab. Project/SDG No.: ____FA35794_____ No. of Samples: _____8_ Trip blank No.: ______FA35794-7____ Field blank No.: _______ Equipment blank No.:_____FA35794-6____ Field duplicate No.:____FA35794-2/ FA35794-3 X___ Data Completeness X___Laboratory Control Spikes X___ Holding Times __X__ Field Duplicates X GC/MS Tuning X Calibrations X Internal Standard Performance X___ Compound Identifications X___ Blanks __X___ Compound Quantitation X___ Surrogate Recoveries X Quantitation Limits X___ Matrix Spike/Matrix Spike Duplicate _OverallComments:___Selected_VOA_from_the_TCL_list_(SW846_8260C)_____ Definition of Qualifiers: J-Estimated results U-Compound not detected R-Rejected data Estimated nondetect UJ-Reviewer: Date: __August_15_2016

DATA COMPLETENESS

MISSING INFORMATION	DATE LAB. CONTACTED	DATE RECEIVED
- 3		
	- A	
(

All criteria were metX	
Critena were not met	
and/or see below	

HOLDING TIMES

The objective of this parameter is to ascertain the validity of the results based on the holding time of the sample from time of collection to the time of analysis.

Complete table for all samples and note the analysis and/or preservation not within criteria

SAMPLE ID	DATE SAMPLED	DATE ANALYZED	pН	ACTION
All samples ana	lyzed within method red	commended holding tim	ne. Samp	les properly preserved.
	27-			

<u>Criteria</u>

Aqueous samples – 14 days from sample collection for preserved samples (pH \leq 2, 4 \pm 2°C), no air bubbles.

Aqueous samples – 7 days from sample collection for unpreserved samples, 4°C, no air bubbles.

Soil samples- 14 days from sample collection.

Cooler temperature (Criteria: 4 ± 2 °C): 4° C - OK

Actions

Aqueous samples

- a. If there is no evidence that the samples were properly preserved (pH < 2, T = 4°C \pm 2°C), but the samples were analyzed within the technical holding time [7 days from sample collection], no qualification of the data is necessary.
- b. If there is no evidence that the samples were properly preserved, and the samples were analyzed outside of the technical holding time [7 days from sample collection], qualify detects for all volatile compounds as estimated (J) and non-detects as unusable (R).
- c. If the samples were properly preserved, and the samples were analyzed within the technical holding time [14 days from sample collection], no qualification of the data is necessary.
- d. If the samples were properly preserved, but were analyzed outside of the technical holding time [14 days from sample collection], qualify detects as estimated (J) and non-detects as unusable (R).
- e. If air bubbles were present in the sample vial used for analysis, qualify detected compounds as estimated (UJ) and non-detected compounds as estimated (UJ).

Non-aqueous samples

- a. If there is no evidence that the samples were properly preserved (T < -7°C or T = 4°C \pm 2°C and preserved with NaHSO₄), but the samples were analyzed within the technical holding time [14 days from sample collection], qualify detects for all volatile compounds as estimated (J) and non-detects as (UJ) or unusable (R) using professional judgment.
- b. If the samples were properly preserved, and the samples were analyzed within the technical holding time [14 days from sample collection], no qualification of the data is necessary.
- c. If there is no evidence that the samples were properly preserved, and the samples were analyzed outside of the technical holding time [14 days from sample collection], qualify detects for all volatile compounds as estimated (J) and non-detects as unusable (R).
- d. If the samples were properly preserved, but were analyzed outside of the technical holding time [14 days from sample collection], qualify detects as estimated (J) and non-detects as unusable (R).

Qualify TCLP/SPLP samples

- a. If the TCLP/SPLP ZHE procedure is performed within the extraction technical holding time of 14 days, detects and non-detects should not be qualified.
- b. If the TCLP/SPLP ZHE procedure is performed outside the extraction technical holding time of 14 days, qualify detects as estimated (J) and non-detects as unusable (R).
- c. If TCLP/SPLP aqueous samples and TCLP/SPLP leachate samples are analyzed within the technical holding time of 7 days, detects and non-detects should not be qualified.
- d. If TCLP/SPLP aqueous samples and TCLP/SPLP leachate samples are analyzed outside of the technical holding time of 7 days, qualify detects as estimated (J) and non-detects as unusable (R).

Table 1. Holding Time Actions for Low/Medium Volatile Analyses - Summary

			Action		
Matrix	Preserved Criteria		Detected Associated Compounds	Non-Detected Associated Compounds	
	No	≤ 7 days	No qu	lalification	
	No	> 7 days	J	R	
Aqueous	Yes	≤ 14 days	No qualification		
ł	Yes	> 14 days	J	R	
	No	≤ 14 days	J	Professional judgment, UJ or R	
Non-Aqueous	Yes	≤ 14 days	No qualification		
	Yes/No	> 14 days	J	R	
TCLP/SPLP	Yes	≤ 14 days	No qualification		
TCLP/SPLP	No	> 14 days	J R		

TCLP/SPLP ZHE performed within the 14-day technical holding time		No qualification	
TCLP/SPLP	ZHE performed outside the 14-day technical holding time	J R	
TCLP/SPLP aqueous & TCLP/SPLP leachate Analyzed within 7 days		No qu	alitication
TCLP/SPLP aqueous & TCLP/SPLP leachate Analyzed outside 7 days		J	R
Sample temperature outside 4°C ± 2°C upon receipt at the laboratory		Use profess	ional judgment
Holding times g		J	R

All criteria were met _	_X
Criteria were not met see below	

GC/MS TUNING

The assessment of the tuning results is to determine if the sample instrumentation is within the standard tuning QC limits

__X___The BFB performance results were reviewed and found to be within the specified criteria.

__X___BFB tuning was performed for every 12 hours of sample analysis.

NOTES: All mass spectrometer instrument conditions must be identical to those used during the sample analysis. Background subtraction actions resulting in spectral distortions for the sole purpose of meeting the method specifications are contrary to the Quality Assurance (QA) objectives, and are therefore unacceptable.

NOTES: No data should be qualified based on BFB failure. Instances of this should be noted in the narrative.

All ion abundance ratios must be normalized to m/z 95, the nominal base peak, even though the ion abundance of m/z 174 may be up to 120% that of m/z 95.

Actions:

If samples are analyzed without a preceding valid instrument performance check, qualify all data in those samples as unusable (R).

If ion abundance criteria are not met, professional judgment may be applied to determine to what extent the data may be utilized. When applying professional judgment to this topic, the most important factors to consider are the empirical results that are relatively insensitive to location on the chromatographic profile and the type of instrumentation. Therefore, the critical ion abundance criteria for BFB are the m/z 95/96, 174/175, 174/176, and 176/177 ratios. The relative abundances of m/z 50 and 75 are of lower importance. This issue is more critical for Tentatively Identified Compounds (TICs) than for target analytes.

Note: State in the Data Review Narrative, decisions to use analytical data associated with BFB instrument performance checks not meeting contract requirements.

Note: Verify that that instrument instrument performance check criteria were achieved using techniques described in Low/Medium Volatiles Organic Analysis, Section II.D.5 of the SOM02.2 NFG, obtain additional information on the instrument performance checks. Make sure that background subtraction was performed from the BFB peak and not from background subtracting from the solvent front or from another region of the chromatogram.

Use professional judgment to determine whether associated data should be qualified based on the spectrum of the mass calibration compound.					
List	the	samples	affected:		
15 32 4	n is in arror all accordated d				

If mass calibration is in error, all associated data are rejected.

All criteria were met _	_X	
Criteria were not met		
and/or see below		

CALIBRATION VERIFICATION

Compliance requirements for satisfactory instrument calibration are established to ensure that the instrument is capable of producing and maintaining acceptable quantitative data.

Date of initial calibration:07/26/16	_
Dates of continuing (initial) calibration:07/26/16	
Dates of continuing calibration:08/01/16;_08/02/16	
Dates of ending calibration: 08/01/16; 08/02/16	
Instrument ID numbers: GCMSJ	
Matrix/Level:Aqueous/low	_

DATE	LAB ID#	FILE	CRITERIA OUT RFs, %RSD, %D, r	COMPOUND	SAMPLES AFFECTED
	_				

Note: Initial calibration, initial calibration verification, and continuing calibration verification within the method and validation guidance document required performance criteria. Closing calibration check verification included in data package.

Criteria

The analyte calibration criteria in the following Table must be obtained. Analytes not meeting the criteria are qualified.

A separate worksheet should be filled for each initial curve

Initial Calibration - Table 2. RRF, %RSD, and %D Acceptance Criteria for Initial Calibration and CCV for Low/Medium Volatile Analysis

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D ¹	Closing Maximum %D
Dichlorodifluoromethane	0.010	25.0	±40.0	±50.0
Chloromethane	0.010	20.0	±30.0	±50.0
Vinyl chloride	0.010	20.0	±25.0	±50.0
Bromomethane	0.010	40.0	±30.0	±50.0
Chloroethane	0.010	40.0	±25.0	±50.0
Trichlorofluoromethane	0.010	40.0	±30.0	±50.0
1,1-Dichloroethene	0.060	20.0	±20.0	±25.0
1,1,2-Trichloro-1,2,2-trifluoroethane	0.050	25.0	±25.0	±50.0
Acetone	0.010	40.0	±40.0	±50.0
Carbon disulfide	0.100	20.0	±25.0	±25.0
Methyl acetate	0.010	40.0	±40.0	±50.0
Methylene chloride	0.010	40.0	±30.0	±50.0
trans-1,2-Dichloroethene	0.100	20.0	±20.0	±25.0
Methyl tert-butyl ether	0.100	40.0	±25.0	±50.0
1,1-Dichloroethane	0.300	20.0	±20.0	±25.0
cis-1,2-Dichloroethene	0.200	20.0	±20.0	±25.0
2-Butanone	0.010	40.0	±40.0	±50.0
Bromochloromethane	0.100	20.0	±20.0	±25.0
Chloroform	0.300	20.0	±20.0	±25.0
1,1,1-Trichloroethane	0.050	20.0	±25.0	±25.0
Cyclohexane	0.010	40.0	±25.0	±50.0
Carbou tetrachloride	0.100	20.0	±25.0	±25.0
Benzene	0.200	20.0	±20.0	±25.0
1,2-Dichloroethaue	0.070	20.0	±20.0	±25.0
Trichloroethene	0.200	20.0	±20.0	±25.0
Methylcyclohexane	0.050	40.0	±25.0	±50.0
1,2-Dichloropropane	0.200	20.0	±20.0	±25.0
Bromodichloromethane	0.300	20.0	±20.0	±25.0
cis-1,3-Dichloropropene	0.300	20.0	±20.0	±25.0
4-Methyl-2-pentanone	0.030	25.0	±30.0	±50.0
Toluene	0.300	20.0	±20.0	±25.0
trans-1,3-Dichloropropene	0.200	20.0	±20.0	±25.0
1,1,2-Trichloroethane	0.200	20.0	±20.0	±25.0
Tetrachloroethene	0.100	20.0	±20.0	±25.0
2-Hexanone	0.010	40.0	±40.0	±50.0
Dibromochloromethane	0.200	20.0	±20.0	±25.0
1,2-Dibromoethane	0.200	20.0	±20.0	±25.0
Chlorobenzene	0.400	20.0	±20.0	±25.0
Ethylbenzene	0.400	20.0	±20.0	±25.0

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D ¹	Closing Maximum
m.p-Xylene	0.200	20.0	±20.0	±25.0
o-Xylene	0,200	20.0	±20.0	±25.0
Styrene	0.200	20.0	±20.0	±25.0
Bromoform	0.100	20.0	±25.0	±50.0
Isopropylbenzene	0,400	20,0	±25.0	±25.0
1,1,2,2-Tetrachloroethane	0.200	20.0	±25.0	±25.0
1,3-Dichlorobenzene	0.500	20.0	±20.0	±25.0
1,4-Dichlorobenzene	0.600	20.0	±20.0	±25.0
1,2-Dichlorobenzene	0,600	20,0	±20.0	±25.0
1,2-Dibromo-3-chloropropane	0.010	25.0	±30.0	±50.0
1,2,4-Trichlorobenzene	0.400	20.0	±30.0	±50.0
1,2,3-Trichlorobenzene	0.400	25.0	±30.0	±50.0
Deuterated Monitoring Compound				
Vinyl chloride-da	0.010	20,0	±30.0	±50.0
Chloroethane-ds	0.010	40.0	±30.0	±50.0
1,1-Dichloroethene-d2	0.050	20.0	±25.0	±25.0
2-Butanone-ds	0.010	40.0	±40.0	±50.0
Chloroform-d	0.300	20.0	±20.0	±25.0
1.2-Dichloroethane-d4	0.060	20.0	±25.0	±25.0
Benzene-da	0,300	20.0	±20.0	±25.0
1,2-Dichloropropaue-do	0.200	20.0	±20.0	±25.0
Toluene-ds	0.300	20.0	±20.0	±25.0
trans-1.3-Dichloropropene-ds	0.200	20.0	±20.0	±25.0
2-Hexanone-ds	0.010	40.0	±40.0	±50.0
1,1,2,2-Tetrachloroethane-d2	0.200	20.0	±25.0	±25.0
1,2-Dichlorobenzene-d4	0.400	20.0	±20.0	±25.0

If a closing CCV is acting as an opening CCV, all target analytes and DMCs must meet the requirements for an opening CCV.

Actions:

- 1. If any volatile target compound has an RRF value less than the minimum in the table, use professional judgment for detects, based on mass spectral identification, to qualify the data as estimated (J+ or R).
 - a. If any volatile target compound has an RRF value less than the minimum criterion, qualify non-detected compounds as unusable (R).
 - b. If any of the volatile target compounds listed in the Table has %RSD greater than the criteria, qualify detects as estimated (J), and non-detected compounds using professional judgment.
 - c. If the volatile target compounds meet the acceptance criteria for RRF and the %RSD, no qualification of the data is necessary.

- d. No qualification of the data is necessary on the DMC RRF and %RSD data alone. Use professional judgment and follow the guidelines in Action 2 to evaluate the DMC RRF and %RSD data in conjunction with the DMC recoveries to determine the need for qualification of data.
- 2. At the reviewer's discretion, and based on the project-specific Data Quality Objectives (DQOs), a more in-depth review may be considered using the following guidelines:
 - a. If any volatile target compound has a %RSD greater than the maximum criterion in the Table, and if eliminating either the high or the low-point of the curve does not restore the %RSD to less than or equal to the required maximum:
 - i. Qualify detects for that compound(s) as estimated (J).
 - ii. Qualify non-detected volatile target compounds using professional judgment.
 - b. If the high-point of the curve is outside of the linearity criteria (e.g., due to saturation):
 - i. Qualify detects outside of the linear portion of the curve as estimated (J).
 - ii. No qualifiers are required for detects in the linear portion of the curve.
 - iii. No qualifiers are required for volatile target compounds that were not detected.
 - c. If the low-point of the curve is outside of the linearity criteria:
 - i. Qualify low-level detects in the area of non-linearity as estimated (J).
 - ii. No qualifiers are required for detects in the linear portion of the curve.
 - iii. For non-detected volatile compounds, use the lowest point of the linear portion of the curve to determine the new quantitation limit.

Note: If the laboratory has failed to provide adequate calibration information, inform the Region's designated representative to contact the laboratory and request the necessary information. If the information is not available, the reviewer must use professional judgment to assess the data.

State in the Data Review Narrative, if possible, the potential effects on the data due to calibration criteria exceedance.

Note, for the Laboratory COR action, if calibration criteria are grossly exceeded.

Table. Initial Calibration Actions for Low/Medium Volatile Analysis - Summary

Criteria	Action		
Criteria	Detect	Non-detect	
Initial Calibration not performed at specified frequency and sequence	Use professional judgment R	Use professional judgment R	
Initial Calibration not performed at the specified concentrations	J	UJ	
RRF = Minimum RRF in Table for target analyte	Use professional judgment J+ or R	R	
RRF > Minimum RRF in Table for target analyte	No qualification	No qualification	
*•RSD > Maximum *•RSD in Table for target analyte	J	Use professional	
*•RSD = Maximum *•RSD in Table for target analyte	No qualification	No qualification	

All criteria were met _X
Criteria were not met
and/or see below

Continuing Calibration Verification (CCV)

NOTE: Verify that the CCV was run at the required frequency (an opening and closing CCV must be run within 12-hour period) and the CCV was compared to the correct initial calibration. If the mid-point standard from the initial calibration is used as an opening CCV, verify that the result (RRF) of the mid-point standard was compared to the average RRF from the correct initial calibration.

The closing CCV used to bracket the end of a 12-hour analytical sequence may be used as the opening CCV for the new 12-hour analytical sequence, provided that all the technical acceptance criteria are met for an opening CCV (see criteria show before in the Table) . If the closing CCV does not meet the technical acceptance criteria for an opening CCV, then a BFB tune followed by an opening CCV is required and the next 12-hour time period begins with the BFB tune.

All DMCs must meet RRF criteria. No qualification of the data is necessary on the DMCs RRF and %RSD/%D data alone. However, use professional judgment to evaluate the DMC and %RSD/%D data in conjunction with the DMC recoveries to determine the need of qualification the data.

Action:

- 1. If a CCV (opening and closing) was not run at the appropriate frequency, qualify data using professional judgment.
- 2. Qualify all volatile target compounds in Table shown before using the following criteria:
 - a. For an opening CCV, if any volatile target compound has an RRF value less than the minimum criterion, use professional judgment for detects, based on mass spectral identification, to qualify the data as estimated (J) and qualify non-detected compounds as unusable (R).
 - b. For a closing CCV, if any volatile target compound has an RRF value less than the criteria, use professional judgment for detects based on mass spectral identification to qualify the data as estimated (J), and qualify non-detected compounds as unusable (R).
 - c. For an opening CCV, if the Percent Difference value for any of the volatile target compounds is outside the limits in calibration criteria Table shown before, qualify detects as estimated (J) and non-detected compounds as estimated (UJ).
 - For a closing CCV, if the Percent Difference value for any volatile target compound is outside the limits in calibration criteria table, qualify detects as estimated (J) and non-detected compounds as estimated (UJ).
 - e. If the volatile target compounds meet the acceptable criteria for RRF and the Percent Difference, no qualification of the data is necessary.

f. No qualification of the data is necessary on the DMC RRF and the Percent Difference data alone. Use professional judgment to evaluate the DMC RRF and Percent Difference data in conjunction with the DMC recoveries to determine the need for qualification of data.

Notes: If the laboratory has failed to provide adequate calibration information, inform the Region's designated representative to contact the laboratory and request the necessary information. If the information is not available, the reviewer must use professional judgment to assess the data.

State in the Data Review Narrative, if possible, the potential effects on the data due to calibration criteria exceedance.

Note, for Contract Laboratory COR action, if calibration criteria are grossly exceeded.

Table. Continuing Calibration Actions for Low/Medium Volatile Analysis – Summary

Criteria for Opening	Criteria for	Action	
CCV	Closing CCV	Detect	Non-detect
CCV not performed at required frequency	CCV not performed at required frequency	Use professional judgment R	Use professional judgment R
CCV not performed at specified concentration	CCV not performed at specified concentration	Use professional judgment	Use professional judgment
RRF < Minimum RRF in Table 2 for target analyte	RRF < Minimum RRF in Table for target analyte	Use professional judgment J or R	R
RRF ≥ Minimum RRF in Table 2 for target analyte	RRF ≥ Minimum RRF in Table for target analyte	No qualification	No qualification
%D outside the Opening Maximum %D limits in Table 2 for target analyte	%D outside the Closing Maximum %D limits in Table for target analyte	J	UJ
% D within the inclusive Opening Maximum % D limits in Table 2 for target analyte	%D within the inclusive Closing Maximum %D limits in Table for target analyte	No qualification	No qualification

All criteria were metX Criteria were not met and/or see below
e existence and magnitude of ly to blanks associated with the s with any blanks exist, all data ether or not there is an inherent rrence not affecting other data.
must be treated separately.
exceed its Contract Required setone, and 2-Butanone). TIC L for TCLP leachate) and ≤ 5.0
echnical acceptance criteria for
CONCENTRATION UNITS
his data in a similar fashion as
CONCENTRATION UNITS

BLANK ANALYSIS RESULTS (Sections 1 & 2)

LADID

The assessment of the blank analysis results is to determine the existence and magnitude of contamination problems. The criteria for evaluation of blanks apply only to blanks associated with the samples, including trip, equipment, and laboratory blanks. If problems with any blanks exist, all data associated with the case must be carefully evaluated to determine whether or not there is an inherent variability in the data for the case, or if the problem is an isolated occurrence not affecting other data.

List the contamination in the blanks below. High and low levels blanks must be treated separately.

The concentration of a target analyte in any blank must not exceed its Contract Required Quantitation Limit (CRQL) (2x CRQLs for Methylene chloride, Acetone, and 2-Butanone). TIC concentration in any blanks must be $\leq 5.0 \,\mu\text{g/L}$ for water (0.0050 mg/L for TCLP leachate) and $\leq 5.0 \,\mu\text{g/kg}$ for soil matrices.

Laboratory blanks

DATE

The method blank, like any other sample in the SDG, must meet the technical acceptance criteria for sample analysis.

COMPOUND

LEVELA

ANALYZED	LADID	MATRIX	COMPOUND	UNITS
Field/ <u>Equipme</u>				
If field or trip blathe method blar	•	nt, the data revie	ewer should evaluate th	iis data in a similar fashion as
DATE Analyzed	LAB ID	LEVEL/ MATRIX	COMPOUND	CONCENTRATION UNITS
45.7	•		pment_blanksNo_field	d_blank_analyzed_with_this
	- N			

All criteria were metX
Criteria were not met
and/or see below

BLANK ANALYSIS RESULTS (Section 3)

Blank Actions

Note:

All fields blank results associated with a particular group of samples (may exceed one per case) must be used to qualify data. Trip blanks are used to qualify only those samples with which they were shipped. Blanks may not be qualified because of contamination in another blank. Field blanks and trip blanks must be qualified for system monitoring compounds, instrument performance criteria, and spectral or calibration QC problems.

Samples taken from a drinking water tap do not have associated field blanks.

When applied as described in the Table below, the contaminant concentration in the blank is multiplied by the sample dilution factor.

Table. Blank and TCLP/SPLP LEB Actions for Low/Medium Volatile Analysis

Blank Type	Blank Result	Sample Result	Action for Samples
	Detects	Not detected	No qualification required
	CDOL *	< CRQL*	Report CRQL value with a U
	< CRQL *	≥ CRQL*	No qualification required
Method,		< CRQL*	Report CRQL value with a U
Storage, Field,		≥ CRQL* and ≤	Report blank value for sample
Trip, TCLP/SPLP LEB,	> CRQL *	blank concentration	concentration with a U
		≥ CRQL* and >	No qualification required
		blank concentration	140 quantication required
Instrument**	= CRQL*	≤ CRQL*	Report CRQL value with a U
	- CRQL	> CRQL*	No qualification required
	Gross	Detects	Report blank value for sample
	contamination	Delects	concentration with a U

^{* 2}x the CRQL for methylene chloride, 2-butanone and acetone.

Action Levels (ALs) should be based upon the highest concentration of contaminant determined in any blank. Do not qualify any blank with another blank. The ALs for samples which have been diluted should be corrected for the sample dilution factor and/or % moisture, where applicable. No positive sample results should be reported unless the concentration of the compound in the samples exceeds the ALs:

^{**} Qualifications based on instrument blank results affect only the sample analyzed immediately after the sample that has target compounds that exceed the calibration range or non-target compounds that exceed 100 µg/L.

Notes:

High and low level blanks must be treated separately Compounds qualified "U" for blank contamination are still considered "hits" when qualifying for calibration criteria.

CONTAMINATION SOURCE/LEVEL	COMPOUND	CONC/UNITS	AL/UNITS	SQL	AFFECTED SAMPLES
	_		ļ i		and distance.
					-0.00
				oralli .	
		Î			
		Ansa			
	- 140.				
· · · · · · · · · · · · · · · · · · ·		Dec.			
	i i				
Name of Street					
95V-				-	

All criteria were metX
Criteria were not met
and/or see below

DEUTERATED MONITORING COMPOUNDS (DMCs)

Laboratory performance of individual samples is established by evaluation of surrogate spike (DMCs) recoveries. All samples are spiked with surrogate compounds prior to sample analysis. The accuracy of the analysis is measured by the surrogate percent recovery. Since the effects of the sample matrix are frequently outside the control of the laboratory and may present relatively unique problems, the validation of data is frequently subjective and demands analytical experience and professional judgment.

Table. Volatile Deuterated Monitoring Compounds (DMCs) and Recovery Limits

DMC	%R for Water Sample	%R for Soil Sample
Vinyl chloride-d3	60-135	30-150
Chloroethane-d5	70-130	30-150
1,1-Dichloroethene-d2	60-125	45-110
2-Butanone-d5	40-130	20-135
Chloroform-d	70-125	40-150
1,2-Dichloroethane-d4	70-125	70-130
Benzene-d6	70-125	20-135
1,2-Dichloropropane-d6	70-120	70-120
Toluene-d8	80-120	30-130
trans-1,3-	60-125	30-135
Dichloropropene-d4		
2-Hexanone-d5	45-130	20-135
1,1,2,2-	65-120	45-120
Tetrachloroethane-d2		
1,2-Dichlorobenzene-d4	80-120	75-120

NOTE: The recovery limits for any of the compounds listed in the above Table may be expanded at any time during the period of performance if the United States Environmental Protection Agency (EPA) determines that the limits are too restrictive.

Action:

Are recoveries for DMCs in volatile samples and blanks must be within the limits specified in the Table above.

Yes? or No?

NOTE: The recovery limits for any of the compounds listed in the Table above may be expanded at any time during the period of performance if USEPA determines that the limits are too restrictive.

List the DMCs that may fail to meet the recovery limits

Sample ID	Date	DMCs	% Recovery	Action
	11-1			

DMCs recoveries within the required limits and within the guidance document performance criteria (80 – 120). Other non-deuterated surrogates added to the samples within laboratory control limits.

Note: Any sample which has more than 3 DMCs outside the limits must be reanalyzed.

Action:

- 1. For any recovery greater than the upper acceptance limit:
 - a. Qualify detected associated volatile target compounds as estimated high (J+).
 - b. Do not qualify non-detected associated volatile target compounds.
- 2. For any recovery greater than or equal to 10%, and less than the lower acceptance limit:
 - Qualify detected associated volatile target compounds as estimated low (J-).
 - Qualify non-detected associated volatile target compounds as estimated (UJ).
- 3. For any recovery less than 10%:
 - Qualify detected associated volatile target compounds as estimated low (J-).
 - b. Qualify non-detected associated volatile target compounds as unusable (R).
- 4. For any recovery within acceptance limits, no qualification of the data is necessary.
- In the special case of a blank analysis having DMCs out of specification, the reviewer must give special consideration to the validity of associated sample data. The basic concern is whether the blank problems represent an isolated problem with the blank alone, or whether there is a fundamental problem with the analytical process. For example, if one or more samples in the batch show acceptable DMC recoveries, the reviewer may choose to consider the blank problem to be an isolated occurrence. However, even if this judgment allows some use of the affected data, note analytical problems for Contract Laboratory COR action.
- 6. If more than three DMCs are outside of the recovery limits for Low/Medium volatiles analysis and the sample was not reanalyzed, note under Contract Problems/Non-Compliance.

Table. Deuterated Monitoring Compound (DMC) Recovery Actions for Low/Medium Volatiles Analyses – Summary

	Action		
Criteria	Detect Associated Compounds	Non-detected Associated Compounds	
%R < 10%	J-	R	
10% ≤ %R < Lower Acceptance Limit	J-	UJ	
Lower Acceptance Limit $\leq \%R \leq Upper$ Acceptance Limit	No qualification	No qualification	
%R > Upper Acceptance Limit	J+	No qualification	

TABLE. VOLATILE DEUTERATED MONITORING COMPOUNDS (DMCs) AND THE ASSOCIATED TARGET COMPOUNDS

Vinyl chloride-ds (DMC-1)	Chloroethane-ds (DMC-2)	1,1-Dichloroethene-d2 (DMC-3)
Vinyl chloride	Dichlorodifluoromethane Chloromethane Bromomethane Chloroethane Carbon disulfide	trans-1,2-Dichloroethene cis-1,2-Dichloroethene 1,1-Dichloroethene
2-Butanone-ds (DMC-4) Acetone 2-Butanone	Chloroform-d (DMC-5) 1,1-Dichloroethane Bromochloromethane Chloroform Dibromochloromethane Bromoform	1,2-Dichloroethane-d4 (DMC-6) Trichlorofluoromethane 1,1,2-Trichloro-1,2,2-trifluoroethane Methyl acetate Methylene chloride Methyl-tert-butyl ether 1,1,1-Trichloroethane Carbon tetrachloride 1,2-Dibromoethane 1,2-Dichloroethane
Benzene-ds (DMC-7)	1,2-Dichloropropane-ds (DMC-8)	Toluene-da (DMC-9)
Benzene	Cyclohexane Methylcyclohexane 1,2-Dichloropropane Bromodichloromethane	Trichloroethene Toluene Tetrachloroethene Ethylbenzene o-Xylene m.p-Xylene Styrene Isopropylbenzene
trans-1,3-Dichloropropene-da (DMC-10)	2-Hexanone-ds (DMC-11)	1,1,2,2-Tetrachloroethane-d2 (DMC-12)
cis-1,3-Dichloropropene trans-1,3-Dichloropropene 1,1,2-Trichloroethane	4-Methyl-2-pentanone 2-Hexanone	1,1,2,2,-Tetrachloroethane 1,2-Dibromo-3-chloropropane
1,2-Dichiorobenzene-d4 (DMC-13) Chlorobenzene 1,3-Dichlorobenzene 1,4-Dichlorobenzene 1,2-Dichlorobenzene 1,2,4-Trichlorobenzene 1,2,3-Trichlorobenzene		

All criteria were met
Criteria were not met
and/or see belowX

MATRIX SPIKE/MATRIX SPIKE DUPLICATE (MS/MSD)

This data is generated to determine long term precision and accuracy in the analytical method for various matrices. This data alone cannot be used to evaluate the precision and accuracy of individual samples. If any % R in the MS or MSD falls outside the designated range, the reviewer should determine if there are matrix effects, i.e. LCS data are within the QC limits but MS/MSD data are outside QC limit.

NOTES:

Data for MS and MSDs will not be present unless requested by the Region. Notify the Contract Laboratory COR if a field or trip blank was used for the MS and MSD.

For a Matrix Spike that does not meet criteria, apply the action to only the field sample used to prepare the Matrix Spike sample. If it is clearly stated in the data validation materials that the samples were taken through incremental sampling or some other method guaranteeing the homogeneity of the sample group, then the entire sample group may be qualified.

1. MS/MSD Recoveries and Precision Criteria

The laboratory should use one MS and a duplicate analysis of an unspiked field sample if target analytes are expected in the sample. If target analytes are not expected, MS/MSD should be analyzed.

List the %Rs, RPD of the compounds which do not meet the criteria.

Sample ID:_	FA35807-1MS/1MSD	Matrix/Level:	Aqueous

Note: MS/MSD % recoveries and RPD within laboratory control limits.

Note:

- * QC limits are laboratory in-house performance criteria, LL = lower limit, UL = upper limit.
- * If QC limits are not available, use limits of 70 130 %.

Actions:

1. No qualification of the data is necessary on MS and MSD data alone. However, using professional judgment, the validator may use the MS and MSD results in conjunction with other QC criteria and determine the need for some qualification of the data.

QUALITY	%R < LL	%R > UL
Positive results	J	J
Nondetects results	R	Accept

MS/MSD criteria apply only to the unspiked sample, its dilutions, and the associated MS/MSD samples:

If the % R for the affected compounds were < LL (or 70 %), qualify positive results (J) and nondetects (UJ).

If the % R for the affected compounds were > UL (or 130 %), only qualify positive results (J).

If 25 % or more of all MS/MSD %R were < LL (or 70 %) or if two or more MS/MSD %Rs were < 10%, qualify all positive results (J) and reject nondetects (R).

A separate worksheet should be used for each MS/MSD pair.

All criteria were metX
Criteria were not met
and/or see below

LABORATORY CONTROL SAMPLE (LCS) ANALYSIS

This data is generated to determine accuracy of the analytical method for various matrices.

1. LCS Recoveries Criteria

Where LCS spiked with the same analyte at the same concentrations as the MS/MSD? **Yes** or No. If no make note in data review memo.

List the %R of compounds which do not meet the criteria

	LCS ID	COMPOUND	% R	QC LIMIT
_Recoveries	_(blank_spike)_	within_laboratory_control_lii	mits	

Note:

- * QC limits are laboratory in-house performance criteria, LL = lower limit, UL = upper limit.
- * If QC limits are not available, use limits of 70 130 %.

Actions:

QUALITY	%R < LL	%R > UL
Positive results	J	J
Nondetects results	R	Accept

All analytes in the associated sample results are qualified for the following criteria.

If 25 % of the LCS recoveries were < LL (or 70 %), qualify all positive results (j) and reject nondetects (R).

If two or more LCS were below 10 %, qualify all positive results as (J) and reject nondetects (R).

2. Frequency Criteria:

Where LCS analyzed at the required frequency and for each matrix? Yes or No. If no, the data may be affected. Use professional judgment to determine the severity of the effect and qualify data accordingly. Discuss any actions below and list the samples affected.

All criteria were metX
Criteria were not met
and/or see below

IX. FIELD/LABORATORY DUPLICATE PRECISION

Sample IDs:FA35794-2/FA35794-3 Matrix:Groundwater	s:FA35794-2/FA35794-3	Matrix:Groundwater
---	-----------------------	--------------------

Field/laboratory duplicates samples may be taken and analyzed as an indication of overall precision. These analyses measure both field and lab precision; therefore, the results may have more variability than laboratory duplicates which only laboratory performance. It is also expected that soil duplicate results will have a greater variance than water matrices due to difficulties associated with collecting identical field duplicate samples.

The project QAPP should be reviewed for project-specific information.

NOTE: In the absence of QAPP guidance for validating data from field duplicates, the following action will be taken.

Identify which samples within the data package are field duplicates. Estimate the relative percent difference (RPD) between the values for each compound. Use professional judgment to note large RPDs (> 50%) in the narrative.

COMPOUND	SQL	SAMPLE CONC.	DUPLICATE CONC.	RPD	ACTION
Benzene	5.0	ND	4.2	•	No action taken, sample/duplicate concentrations < 5 x SQL.

Field/laboratory duplicate analyzed with this data package. PRD within required criteria, \leq 50 % for target analytes detected at concentration > 5x the SQL or the reporting in sample and duplicate except for the cases described in this document.

Actions:

Qualify as estimated positive results (J) and nondetects (UJ) for the compound that exceeded the above criteria. For organics, only the sample and duplicate will be qualified.

If an RPD cannot be calculated because one or both of the sample results is not detected, the following actions are suggested based on professional judgment:

If one sample result is not detected and the other is greater than 5x the SQL qualify (J/UJ).

If one sample value is not detected and the other is greater than 5x the SQL and the SQLs for the sample and duplicate are significantly different, use professional judgment to determine if qualification is appropriate.

If one sample value is not detected and the other is less than 5x, use professional judgment to determine if qualification is appropriate.

If both sample and duplicate results are not detected, no action is needed.

All criteria were metX
Criteria were not met
and/or see below

X. INTERNAL STANDARD PERFORMANCE

The assessment of the internal standard (IS) parameter is used to assist the data reviewer in determining the condition of the analytical instrumentation.

DATE SAMPLE ID IS OUT IS AREA ACCEPTABLE ACTION RANGE

Internal standard area counts within the required criteria for all samples.

Action:

- If an internal standard area count for a sample or blank is greater than 200.0% of the area for the associated standard (opening CCV or mid-point standard from initial calibration) (see Table below):
 - a. Qualify detects for compounds quantitated using that internal standard as estimated low (J-).
 - b. Do not qualify non-detected associated compounds.
- 2. If an internal standard area count for a sample or blank is less than 20.0% of the area for the associated standard (opening CCV or mid-point standard from initial calibration):
 - a. Qualify detects for compounds quantitated using that internal standard as estimated high (J+).
 - Qualify non-detected associated compounds as unusable (R).
- If an internal standard area count for a sample or blank is greater than or equal to 20.0%, and less than or equal to 200% of the area for the associated standard opening CCV or midpoint standard from initial calibration, no qualification of the data is necessary.
- 4. If an internal standard RT varies by more than 30.0 seconds: Examine the chromatographic profile for that sample to determine if any false positives or negatives exist. For shifts of a large magnitude, the reviewer may consider partial or total rejection of the data for that sample fraction. Detects should not need to be qualified as unusable (R) if the mass spectral criteria are met.
- 5. If an internal standard RT varies by less than or equal to 30.0 seconds, no qualification of the data is necessary.

Note: Inform the Contract Laboratory Program Project Officer (CLP PO) if the internal standard performance criteria are grossly exceeded. Note in the Data Review Narrative potential effects on the data resulting from unacceptable internal standard performance.

- 6. If required internal standard compounds are not added to a sample or blank, qualify detects and non-detects as unusable (R).
- 7. If the required internal standard compound is not analyzed at the specified concentration in a sample or blank, use professional judgment to qualify detects and non-detects.

Table. Internal Standard Actions for Low/Medium Volatiles Analyses - Summary

	Action	
Criteria	Detected Associated	Non-detected Associated
	Compounds*	Compounds*
Area counts > 200% of 12-hour standard (opening CCV or	J-	No
	uid-point standard from initial calibration) gualific	
Area counts < 20% of 12-hour standard (opening CCV or mid-point standard from initial calibration)	J+	R
Area counts ≥ 50% but ≤ 200% of 12-hour standard (opening CCV or mid-point standard from initial calibration)	No qualification	
RT difference > 30.0 seconds between samples and 12-hour standard (opening CCV or mid-point standard from initial calibration)	R **	R
RT difference ≤ 30.0 seconds between samples and 12-hour standard (opening CCV or mid-point standard from initial calibration)	No qualification	

^{*} For volatile compounds associated to each internal standard, see TABLE - VOLATILE TARGET ANALYTES, DEUTERATED MONITORING COMPOUNDS WITH ASSOCIATED INTERNAL STANDARDS FOR QUANTITATION in SOM02.2, Exhibit D, available at: http://www.epa.gov/superfund/programs/clp/download/som/som22d.pdf ** Detects should not need to be qualified as unusable (R) if the mass spectral criteria are met.

		All criteria were metX Criteria were not met and/or see below
TARGET COM	MPOUND IDENTIFICATION	
Criteria:		
	ve Retention Times (RRTs) of reported con Γ [opening Continuing Calibration Verification on].	
List compound	ds not meeting the criteria described above:	
Sample ID	Compounds	Actions
spectrum from	of the sample compound and a current labor the associated calibration standard (opening that match according to the following criteria: All ions present in the standard mass spectrum. The relative intensities of these ions must and sample spectra (e.g., for an ion with spectrum, the corresponding sample ion about lons present at greater than 10% in the sample standard spectrum, must be evaluated spectral interpretation.	og CCV or mid-point standard from initial actrum at a relative intensity greater than am. agree within ±20% between the standard an abundance of 50% in the standard bundance must be between 30-70%). Cample mass spectrum, but not present in
List compound	ds not meeting the criteria described above:	
Sample ID	Compounds	Actions

Action:

- 1. The application of qualitative criteria for GC/MS analysis of target compounds requires professional judgment. It is up to the reviewer's discretion to obtain additional information from the laboratory. If it is determined that incorrect identifications were made, qualify all such data as unusable (R).
- 2. Use professional judgment to qualify the data if it is determined that cross-contamination has occurred.
- 3. Note in the Data Review Narrative any changes made to the reported compounds or concerns regarding target compound identifications. Note, for Contract Laboratory COR action, the necessity for numerous or significant changes.

TENTATIVELY IDENTIFIED COMPOUNDS (TICS)

NOTE: Tentatively identified compounds should only be evaluated when requested by a party from outside of the Hazardous Waste Support Section (HWSS).

Sample ID	Compound	Sample ID	Compound
			
		<u> </u>	

Action:

List TICs

- 1. Qualify all TIC results for which there is presumptive evidence of a match (e.g. greater than or equal to 85% match) as tentatively identified (NJ), with approximated concentrations. TICs labeled "unknown" are qualified as estimated (J).
- 2. General actions related to the review of TIC results are as follows:
 - a. If it is determined that a tentative identification of a non-target compound is unacceptable, change the tentative identification to "unknown" or another appropriate identification, and qualify the result as estimated (J).
 - b. If all contractually-required peaks were not library searched and quantitated, the Region's designated representative may request these data from the laboratory.
- 3. In deciding whether a library search result for a TIC represents a reasonable identification, use professional judgment. If there is more than one possible match, report the result as "either compound X or compound Y". If there is a lack of isomer specificity, change the TIC result to a nonspecific isomer result (e.g., 1,3,5-trimethyl benzene to trimethyl benzene

- isomer) or to a compound class (e.g., 2-methyl, 3-ethyl benzene to a substituted aromatic compound).
- 4. The reviewer may elect to report all similar compounds as a total (e.g., all alkanes may be summarized and reported as total hydrocarbons).
- 5. Target compounds from other fractions and suspected laboratory contaminants should be marked as "non-reportable".
- 6. Other Case factors may influence TIC judgments. If a sample TIC match is poor, but other samples have a TIC with a valid library match, similar RRT, and the same ions, infer identification information from the other sample TIC results.
- 7. Note in the Data Review Narrative any changes made to the reported data or any concerns regarding TIC identifications.
- 8. Note, for Contract Laboratory COR action, failure to properly evaluate and report TICs

All criteria were metX_	_
Criteria were not met	
and/or see below	

SAMPLE QUANTITATION AND REPORTED CONTRACT REQUIRED QUANTITATION LIMITS (CRQLS)

Action:

- 1. If any discrepancies are found, the Region's designated representative may contact the laboratory to obtain additional information that could resolve any differences. If a discrepancy remains unresolved, the reviewer must use professional judgment to decide which value is the most accurate. Under these circumstances, the reviewer may determine that qualification of data is warranted. Note in the Data Review Narrative a description of the reasons for data qualification and the qualification that is applied to the data.
- 2. For non-aqueous samples, in the percent moisture is less than 70.0%, no qualification of the data is necessary. If the percent moisture is greater than or equal to 70.0% and less than 90.0%, qualify detects as estimated (J) and non-detects as approximated (UJ). If the percent moisture is greater than or equal to 90.0%, qualify detects as estimated (J) and non-detects as unusable (R) (see Table below).
- 3. Note, for Contract Laboratory COR action, numerous or significant failures to accurately quantify the target compounds or to properly evaluate and adjust CRQLs.
- 4. Results between MDL and CRQL should be qualified as estimated "J".
- 5. Results < MDL should be reported at the CRQL and qualified "U". MDLs themselves are not reported.

Table. Percent Moisture Actions for Low/Medium Volatiles Analysis for Non-Aqueous Samples

Criteria	Action		
	Detected Associated	Non-detected Associated	
	Compounds	Compounds	
% Moisture < 70.0	No qualification		
70.0 < % Moisture < 90.0	J	UJ	
% Moisture > 90.0	J	R	

The sample quantitation evaluation is to verify laboratory quantitation results. In the space below, please show a minimum of one sample calculation:

Sample ID

FA35794-3

Benzene

RF = 1.093

[] = (25462)(50)/(1.093)(1384251) = 0.84 ppb Ok

B.	Percent Solids
	List samples which have ≥ 70 % solids

All criteria were met _X
Criteria were not met
and/or see below

QUANTITATION LIMITS

A. Dilution performed

SAMPLE ID	DILUTION FACTOR	REASON FOR DILUTION
FA35794-3	5 x	Matrix interference; the sample foamed.
20 2000		
		400000
		72
	1000	
		. — 19. — 19. pp 40.4 — 19. — 34. —
	War and the second	
The state of the s		
		50 3507

		Criteria were not met and/or see below
OTHER ISSUES		
A. System Perf	ormance	
List samples qualifie	d based on the degradation of system pe	rformance during simple analysis:
Sample ID	Comments	Actions
Action:		
degraded during sai		ermined that system performance has poratory Program COR any action as a dy affected the data.
B. Overall Asse	ssment of Data	
List samples qualifie	d based on other issues:	
Sample ID	Comments	Actions
No_additional_issu	es_observed_that_require_qualification_	of_the_dataResults_are_valid_and

Action:

- Use professional judgment to determine if there is any need to qualify data which were not qualified based on the Quality Control (QC) criteria previously discussed.
- 2. Write a brief narrative to give the user an indication of the analytical limitations of the data. Inform the Contract Laboratory COR the action, any inconsistency of the data with the Sample Delivery Group (SDG) Narrative. If sufficient information on the intended use and required quality of the data is available, the reviewer should include their assessment of the usability of the data within the given context. This may be used as part of a formal Data Quality Assessment (DQA).